



Advance Single Parameter Analyzer pH, Temp.

Model 6308PT

Improve quality control, reduce process downtime, enhance research and development, meet regulations, all while keeping cost low.

The Right Features To Measure, Analyze And Control pH And Temperature

Accurate and stable readings.

5 programmable on/off relays: 4 for pH and 1 for temperature.

Manual or automatic temperature compensated (ATC) pH readings.

Programmable hysteresis for customized control.

Isolated and reversible 4-20 mA current output for pH. This output can be used as a proportional output.

DC voltage output for pH/ORP pre-amplifier.

RS-485 output for remote access via an IBM compatible computer. This allows multiple units to be connected, ganged, together.

Large, Graphical, Backlit LCD Display

Simultaneous display of: pH, temperature, relay status, electrode efficiency and transmitter current mA output.

Clear, bright LCD with manual backlight switch for added visibility in dark working conditions.

Quick And Easy Setup, Intuitive Operation

Setup and calibration are done through a friendly, user-guided menu.

Convenient calibration with automatic buffer recognition of US and European buffer sets. Calibration data is stored in memory and is ready for use on power up.

Included panel mount bracket tightly secures the analyzer.

Standard ¼ DIN size.

Standard terminal block for tinned leads connectors. Spade lug connector for pH.

Low Maintenance

Performs self-diagnostic at power up to ensure proper operation.

Analyzer is in a complete watertight case (IP65).

Displays electrode efficiency for optimized electrode maintenance.

Membrane keypad with tactile and audio feedback improves durability and usability.

Password protection ensures the right people have access to change settings.

Specifications

Range

pH	- 2.00 to 16.00 pH
Temp	- 10.0 to 120.0 °C

Resolution

pH	0.01 pH
Temp	0.1 °C

Accuracy

pH	± 0.01 pH ± 1 LSD
Temp	± 0.1 °C ± 1 LSD

General

pH:

pH Temp Compensation	Auto -10.0 to 120.0 °C
pH Buffer Recognition	4.00, 4.01, 6.86, 7.00, 9.18, 10.01
pH Buffer Temp. Range	0 to 60 °C
PH Electrode Offset Recognition	± 100 mV at pH 7.00 - 91.7 to +108.3 mV at pH 6.86
pH Electrode Slope Recognition	± 30 % at pH 4.00, 4.01, 9.18 or 10.01
Input Impedance	>10 ¹³ ohms
Calibration End Point Sensing	Yes
Pre-amplifier Output	± 5 V DC

Temperature:

Temperature Sensor	Thermistor, 10.00 k ohm at 25 °C
--------------------	----------------------------------

4-20 mA Analog Output:

Current Output Range	4 to 20 mA (isolated), programmable span
Current Output Scale	User programmable, linear or log
Maximum Load	500 ohm
Accuracy	± 0.02 mA
Isolation Voltage	500 V DC

Relays:

Control Type	5 ON/OFF controls
Relay Output	5 A at 115 V AC or 2.5 A at 220 V AC, resistive load only

Other:

Power Supply	115 V AC or 230 V AC at 50/60 HZ
Security	4-digit password
Audio Feedback	All Touch Keys
Communication	RS-485
Fuse	0.315 A / 250 V fast acting glass tube
Display	128 x 64 graphical LCD with backlight
Ambient Temp. Range	0 to 50 °C
Case	IP65, 1/4 DIN case, 148 mm depth
Weight	950 g

Accessories

General purpose or custom electrodes

NEMA 4 enclosures

